

ThermoPlus AS2

Programmable room thermostat

AS2 is battery-powered for applications where no mains supply is readily available to operate the unit, or an existing thermostat is being replaced.

Additional features include three standard AA batteries, two years+ battery life and separate clock power back-up. Battery life is conserved by means of an eight-second autpower-down mode to all indicator lights. Designed for ease of use, with a unique three button user interface. ThermoPlus allows a high and low temperature setting to be pre-programmed, with simple user overrides available.

ThermoPlus has voltage-free contacts and is ideal for use with combi boilers.



Applications

ThermoPlus can be used with most types of heating system where a simple user interface is beneficial, such as for the elderly and vulnerable.

- Control of most domestic gas or oil-powered central heating systems
- Control of additional heating zones
- Combination ('combi') boilers
- Control of solid-fuel heating systems
- Replacement of existing thermostats

Benefits

- Simple user settings
- Accessibility features for non-sighted users
- Safeguard against hypothermia and frost

Features

- Simple 3-button operation
- Colour coded, bright LED Warm/Cool display and Braille markings on the main override buttons
- Preset clock
- Automatic BST/GMT time change
- Preset or custom heating profiles
- Back-lit LCD display
- Audible and tactile feedback
- Fixed hypothermia protection (PRT1)
- Frost protection
- 7 years no quibbles warranty





Technical specifications

Electrical

Contact rating	3 (1) Amps 230-240V
Contact type	Micro disconnection voltage-free
Reserve battery type	Lithium battery
Supply	3 x AA (LR6) batteries

Environmental

Pollution degree	Degree 2
Double insulated	Yes
Enclosure protection	IP30
Operating temperature range	0 °C to 40 °C
Temperature control range	+5 °C to +30 °C
Standby temperature	+5 °C to +10 °C

Mechanical

Case material	Thermoplastic flame retardant
Dimensions	120 x 90 x 32mm

Features

Display	Liquid crystal, back-lit
Clock	24-hour
Displayed time adjustments	1-minute steps
Switched time adjustments	15-minute steps
Operating periods	Warm – 3 per-day
Programme settings	Auto, Standby
Override	Instant Warm/Cool
Mounting	Standard wall box fixing

Australia

sales_australia@securemeters.com
www.securemeters.com/au

Middle East

sales_middleeast@securemeters.com
www.securemeters.com/me

Europe

sales_europe@securemeters.com
www.securemeters.com/eu

India, Asia, Africa

sales_india@securemeters.com
www.securemeters.com/in

UK

sales_uk@securemeters.com
www.securemeters.com/uk