

# Liberty 370

## Three-phase pre-payment electricity meter



Pay as you go  
(PAYG)



Intuitive



Revenue  
protection

Liberty 370 is a three-phase pre-payment electricity meter that provides information on account balance and consumption patterns, together with alerts and notifications that help consumers save energy and budget effectively. Consumers can easily interact with the meter via a user-friendly mobile app. The Liberty system provides peace of mind to utilities by ensuring completeness of revenue through operational efficiency. It is simple to manage and enables the utility to provide hassle-free consumer services.

The vending system is intuitive, with flexible architecture, to provide integration options with POS terminals, utility web portals, e-wallets / kiosks and through mobile app. The highly secure and robust implementation is designed in accordance with the international ISO 27001 standard.



### Application

- Domestic metering
- Small and medium-scale industries
- Temporary connection metering
- Sub-metering

### Benefits

- Effective energy budgeting through monetary consumption displays
- Hassle-free electricity purchase options and transfer to meter
- No need for separate in-home display unit (IHD)
- Easy meter recharging through mobile app
- Upfront revenue collection and revenue assurance for utility
- Improves billing and collection efficiency
- Break to open meter enclosure to avoid tampering
- Extensive revenue protection features for detection and analysis of tamper attempts
- Long-range meter (10-100A) for all domestic and SME applications

### Features

- Meter with disconnection switches (mechanically ganged)
- Enables data collection over BLE
- Encrypted data using AES128 security
- Authenticated billing code (ABC) with time-stamp
- Easy token transfer over Bluetooth
- Intuitive, user-friendly eight digits display
- Display in absence of mains supply
- Two metrological LEDs for accuracy measurement
- Emergency credit facility to help consumers manage their account
- Quality-of-supply information - voltage monitoring and Customer Average Interruption Duration Index (CAIDI)
- Capacitive touchpad with standard telephone keypad for multiple parameter navigation
- Easy disconnection / settlement mechanism
- Fixed and variable friendly credit days for no disconnection
- Time-of-use (ToU) tariff support for customisable seasons and days



## Technical specifications

### Electrical

|                      |                                 |
|----------------------|---------------------------------|
| Connection type      | Direct connected                |
| Wiring configuration | 3-phase 4-wire                  |
| Voltage reference    | 240 / 230 V (L-N), -40% to +30% |
| Current range        | 10-100 A                        |
| Accuracy             | Class 1.0                       |
| Frequency            | 50 Hz ±5%, 60 Hz ±5%            |

### Compliance

|           |  |
|-----------|--|
| Standards | IS 13779, IS 15884, IS 15959 and IEC62055-31 |
|-----------|--|

### Mechanical

|                        |  |
|------------------------|--|
| Dimensions (W x H x D) | 184 mm x 207 mm x 98 mm<br>(with extended terminal cover)                          |
| Weight                 | 1.5 kg   |
| Enclosure              | Engineering plastic  |
| Sealing                | Sealed for life,<br>additional sealing provision at meter cover and terminal cover |

### Environmental

|                    |  |
|--------------------|--|
| Ingress protection | IP 54  |
| Temperature        | -10 °C to +60 °C (operating)<br>-25 °C to +70 °C (storage) |
| Humidity           | 95%, non-condensing  |

### Features

|                         |   |
|-------------------------|---|
| Tariff                  | Up to 8 rates (slab or time-of-use)                     |
| Maximum demand register | Active and apparent energy                              |
| Load survey             | 240 parameter days with 30-minute integration period    |
| Energy supported        | 7 energy parameters (factory configurable)              |
| Histories               | 12 historical sets of values                            |
| Reading data            | Details for all the energy charges for all 12 histories |

### Communications

|                                       |
|---------------------------------------|
| Optical port for local communications |
| BLE for remote access                 |

**Africa**  
sales\_africa@securemeters.com

**Australia**  
sales\_australia@securemeters.com

**Europe**  
sales\_eu@securemeters.com

**India**  
sales\_india@securemeters.com

**South East Asia, South Asia**  
sales\_sea@securemeters.com

**UAE**  
sales\_uae@securemeters.com

**UK**  
sales\_uk@securemeters.com

[www.securemeters.com](http://www.securemeters.com)